

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED406-102-6D-N1



Dimensions: 26" L x 8" H x 2.25" D. Display real-time information to your employees or customers. The display will up-time in HH:MM:SS (default) when a customer-supplied on/off switch is activated. A separate momentary switch will reset the unit to "00:00:00".

- Dimensions: 26"L x 8"H x 2.25"D
- 4.0" LED Display with Six Digits
- Up-timer in HH:MM:SS format will up-time in seconds with a contact closure and reset to "00:00:00" with another contact.
- Mounting Brackets
- Factory Service One-Year Warranty on Parts and Labor

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at

1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED406-102-6D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 700 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	26" L x 8" H x 2.25" D
Weight	Approx. 8 Lbs.
Number of Digits	Six (6) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 190 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service